


L-09



Profilo per Strip LED tagliabile in opera, per realizzare linee di luce incassate nel cartongesso.
 Corpo in cartongesso di spessore 12,5 mm da lastra standard o HYDRO (a ridotto assorbimento di acqua, utilizzabile in ambienti con umidità relativa costante dell'aria ≤70%).
 Profilo dissipante in lega di alluminio anodizzato naturale e schermo di protezione in PMMA opale inclusi.
 Strip LED e alimentatore elettronico 24Vdc remoto da ordinare a parte.


Profile for Strip LED, for light cut on plasterboard.
 Body made of 12,5 mm thick plasterboard, either standard or HYDRO treated (with reduced water absorption level to be used in environments with constant relative humidity levels of air ≤70%).
 Dissipating profile made of anodized aluminium alloy natural finish and PMMA opal diffuser included.
 Strip LED and remote electronic driver 24Vdc to be ordered separately.



PROFILO LINEARE
LINEAR PROFILE

L Ltot + 5
 W 120


CODE	L (mm)	Version
101898.99	2000	Standard
101899.99	2000	HYDRO



PROFILO ANGOLARE 90°
90° CORNER PROFILE

L 1003x1003
 W 120

CODE	L (mm)	Version
1018A0.99	998x998	Standard
1018A1.99	998x998	HYDRO




L-09 CORNER
 profilo lineare per spigolo esterno
 non installabile direttamente
 su muratura

L-09 CORNER
 linear profile for external corner
 not for direct installation
 on hard surfaces

L Ltot + 5
 W 70x70

CODE	L (mm)	Version
1018A8.99	2000	Standard
1018A9.99	2000	HYDRO



L-09 EDGE
 profilo lineare per spigolo interno

L-09 EDGE
 linear profile for internal corner

L Ltot + 5
 W 73x73

CODE	L (mm)	Version
1018A6.99	2000	Standard
1018A7.99	2000	HYDRO

L-09 WALL

Profilo per Strip LED tagliabile in opera, per realizzare linee di luce incassate in muratura.

Profilo tagliabile in opera in lega di alluminio anodizzata naturale e rete di armatura porta-intonaco in acciaio zincato.

Schermo di protezione in PMMA opale incluso.

Strip LED e alimentatore elettronico remoto da ordinare a parte.


Profile for Strip LED for light cut on concrete or brick surface.

Length cuttable on measure on site.

Profile made of aluminium alloy and galvanized steel grid to plaster.

PMMA protection screen included.

Strip LED and remote electronic driver to be ordered separately.



PROFILO LINEARE


LINEAR PROFILE

CODE L (mm)

1018B0.99	2000
------------------	------

L-09 L-09 WALL

ACCESSORI ACCESSORIES




SCHERMO OPALE 6 m
opzionale
Consigliato per installazioni in fila continua

OPAL SCREEN 6 m
optional
Recommended for continuous line installations

CODE L (mm)

1018A2.99	6000	Opale / Opal
------------------	------	--------------



STRIP LED 4mm
11,5W/m

CODE L (mm) LED COLOUR FLUX/m IP CRI

100913.99	5000	2700K	1050	20	90
100914.99	5000	3000K	1113	20	90
100915.99	5000	4000K	1163	20	90
100928.99	5000	2700K	1016	65	90
100929.99	5000	3000K	1038	65	90
100930.99	5000	4000K	1124	65	90

SMD 2216 (182 LED/m)
Biadesivo - sezionabile ogni 38,4 mm (7 LED)
Biadhesive - cuttable every 38,4 mm (7 LED)