




# LA STAGNA 2.0

Apparecchio LED lineare IP65 per installazione singola o in fila continua. Corpo e testate in policarbonato bianco, schermo coestruso in policarbonato opale rigato.

Alimentazione elettronica 220-240V 50-60Hz integrata, 2 pressacavi per la continuità di linea, terminale per installazioni stand-alone o per chiusura di fila continua e 2 staffe in acciaio armonico per installazione a parete o plafone inclusi. Cavo di alimentazione non incluso, da prevedere con guaina esterna D=5-8 mm.

Linear LED IP65 fixture for stand alone installation or in series system. Body and end caps in white polycarbonate, screen co-extruded polycarbonate opal lined. Electronic power supply 220-240V 50-60Hz integrated, no.2 cord grips for the continuity of line, an appropriate terminal suitable for stand-alone or for closing a continuous line and no.2 brackets for ceiling or wall mounting included. Power cable with outer sheath D=5-8 mm not included.



POWER	L (mm)	FLUX	4000K <input type="checkbox"/>
38W	1225	3810 lm	<b>19401.01</b>
48W	1525	4785 lm	<b>19402.01</b>

## ACCESSORI ACCESSORIES



SOSPENSIONE IN ACCIAIO  
REGOLABILE (1 pz.)  
prevedere n.2 sospensioni per ogni  
apparecchio.

ADJUSTABLE SUSPENSIONS (1 pc)  
necessary No.2 suspensions for  
each appliance.

CODE	L (mm)
<b>18754.99</b>	1200
<b>18755.99</b>	3000

