

LUNA TONDO

19W - 2030lm • 36W - 3910lm



104301.01	- 19W	- 3000K	1928lm
104302.01	- 19W	- 4000K	2030lm
104309.01	- 19W	- 3000K	1928lm sensore di presenza / presence detector
104310.01	- 19W	- 4000K	2030lm sensore di presenza / presence detector
104311.01	- 19W	- 3000K	1928lm emergenza / emergency
104312.01	- 19W	- 4000K	2030lm emergenza / emergency
104303.01	- 36W	- 3000K	3724lm
104304.01	- 36W	- 4000K	3910lm

Tempo di attesa 90s
Soglia diurna 20lux
Hold time 90s
Daylight threshold 20lux

Disponibile da LUGLIO 2018
Available from JULY 2018

1 Ora / 1 Hour

Disponibile da LUGLIO 2018
Available from JULY 2018

_.01 BIANCO/WHITE

44

Apparecchio LED per installazione a plafone o a parete. Disponibili versioni warm white 3000K o neutral white 4000K. Emissione diffusa.

Materiali

Base in policarbonato colore bianco, diffusore in policarbonato ad elevata trasmittanza.

Cablaggi

- Alimentatore elettronico 220-240V 50/60Hz incluso.
- Versione con emergenza 1 ora servizio continuo (H=60mm).
- Versione con sensore di presenza e luminosità.

LED fixture for ceiling or wall surface installation. Available in versions warm white 3000K or neutral white 4000K. Diffuse emission.


Materials

Polycarbonate base in white color. Polycarbonate diffuser with high transmittance.



Wiring

- Electronic 220-240V 50/60Hz driver included.
- 1 Hour emergency continuous service version (H=60mm).
- Presence and brightness sensor version.

19W



36W





LUNA QUADRATO

19W - 2030lm • 36W - 3910lm



104305.01	- 19W	- 3000K	1840lm
104306.01	- 19W	- 4000K	1937lm
104307.01	- 36W	- 3000K	3724lm
104308.01	- 36W	- 4000K	3920lm

_.01 BIANCO/WHITE

Apparecchio LED per installazione a plafone o a parete. Disponibili versioni warm white 3000K o neutral white 4000K. Emissione diffusa.

Materiali
Base in policarbonato colore bianco, diffusore in policarbonato ad elevata trasmittanza.


Cablaggi
Alimentatore elettronico 220-240V 50/60Hz incluso.

LED fixture for ceiling or wall surface installation. Available in versions warm white 3000K or neutral white 4000K. Diffuse emission.



Materials
Polycarbonate base in white color. Polycarbonate diffuser with high transmittance.

Wiring
Electronic 220-240V 50/60Hz driver included.

19W



36W



45