

# MINI WELL


IL PRODOTTO RISPONDEnte AI REQUISITI PER EDIFICI PUBBLICI  
D.M. 11 OTT 2017 (C.A.M. Edilizia)

THE PRODUCT COMPLIES WITH THE REQUIREMENTS FOR  
PUBLIC BUILDINGS, MINISTERIAL DECREE OF 11th OCT 2017



Downlight LED per incasso da rasare, installabile su cartongesso di spessore 5-15 mm.  
Corpo tondo e controltelaio in pressofusione di alluminio verniciato.  
Corpo quadrato e controltelaio in acciaio verniciato. Dissipatore in lega di alluminio anodizzato.  
Alimentatore elettronico 500mA da ordinare a parte.

Frameless LED downlight, to be installed on 5-15 mm thickness plasterboard.  
Round body and subframe in painted die-cast aluminium. Square body and subframe in painted steel. Heat sink in anodized aluminium alloy.  
Electronic driver 500mA to be ordered separately.




**MINI WELL TONDO**  
500mA

UGR <19 \*



POWER	BEAM	FLUX (white - black)	3000K	*
5W	36°	326 - 273 lm	<input type="checkbox"/>	<input checked="" type="checkbox"/>
			<b>101908.01</b>	<b>.02</b>



**MINI WELL QUADRATO**  
500mA


UGR <19 \*



POWER	BEAM	FLUX (white - black)	3000K	*
5W	36°	381 - 365 lm	<input type="checkbox"/>	<input checked="" type="checkbox"/>
			<b>101907.01</b>	<b>.02</b>

# WELL MINI WELL


## ACCESSORI ACCESSORIES



ALIMENTATORE ELETTRONICO  
STABILIZZATO 500mA  
220-240V 50/60Hz  
idoneo per il collegamento in serie  
di max 1 Well o 2 Mini Well.

ELECTRONIC STABILIZED  
DRIVER 500mA  
220-240V 50/60Hz  
Suitable for the connection in series  
of max 1 Well or 2 Mini Well.

CODE	POWER	A (mm)	D (mm)	H (mm)	L (mm)
<b>101307.99</b>	15W	45	49	19	123




ALIMENTATORE ELETTRONICO  
DIMMERABILE STABILIZZATO 500mA  
220-240V 50/60Hz  
idoneo per il collegamento in serie  
di max 2 Well o 4 Mini Well.

Max 10 alimentatori gestibili in PUSH con  
uno o più pulsanti NA in parallelo  
(non necessita di cavetti di sincronizzazione).

ELECTRONIC DIMMABLE  
STABILIZED DRIVER 500mA  
220-240V 50/60Hz  
Suitable for the connection in series  
of max 2 Well or 4 Mini Well.  
Max 10 drivers manageable in PUSH  
with one or more NO buttons in parallel  
(no synchronization cables required).

CODE	POWER	A (mm)	D (mm)	H (mm)	L (mm)
<b>101904.99</b>	20W	52	58	26	156



KIT DI EMERGENZA  
da installare sul controsoffitto  
a lato del prodotto.

EMERGENCY KIT  
to place on the false ceiling  
next to the fixture.

CODE	TIME	A (mm)	D (mm)	H (mm)	L (mm)
<b>18002.99</b>	1h	46	59	23	138
<b>18003.99</b>	3h	80	92	45	212

Flusso in emergenza  
Emergency flux

<b>WELL 10W</b>	<b>67%</b>
<b>MINI WELL 5W</b>	<b>76%</b>