

MINI WELL

IL PRODOTTO RISPONDEnte AI REQUISITI PER EDIFICI PUBBLICI
D.M. 11 OTT 2017 (C.A.M. Edilizia)

THE PRODUCT COMPLIES WITH THE REQUIREMENTS FOR
PUBLIC BUILDINGS, MINISTERIAL DECREE OF 11th OCT 2017



Downlight LED per incasso da rasare, installabile su cartongesso di spessore 5-15 mm.

Corpo tondo e controltelaio in pressofusione di alluminio verniciato.


Corpo quadrato e controltelaio in acciaio verniciato. Dissipatore in lega di alluminio anodizzato.

Alimentatore elettronico 500mA da ordinare a parte.

Frameless LED downlight, to be installed on 5-15 mm thickness plasterboard.

Round body and subframe in painted die-cast aluminium. Square body and subframe in painted steel. Heat sink in anodized aluminum alloy.

Electronic driver 500mA to be ordered separately.




MINI WELL TONDO

500mA

UGR <19 *

POWER	BEAM	FLUX (white - black)	3000K <input type="checkbox"/>	<input checked="" type="checkbox"/> *
5W	36°	326 - 273 lm	101908.01	.02



MINI WELL QUADRATO

500mA



UGR <19 *

POWER	BEAM	FLUX (white - black)	3000K <input type="checkbox"/>	<input checked="" type="checkbox"/> *
5W	36°	381 - 365 lm	101907.01	.02



WELL MINI WELL


ACCESSORI ACCESSORIES



ALIMENTATORE ELETTRONICO
STABILIZZATO 500mA
220-240V 50/60Hz
idoneo per il collegamento in serie
di max 1 Well o 2 Mini Well.

ELECTRONIC STABILIZED
DRIVER 500mA
220-240V 50/60Hz
Suitable for the connection in series
of max 1 Well or 2 Mini Well.

CODE	POWER	A (mm)	D (mm)	H (mm)	L (mm)
101307.99	15W	45	49	19	123




ALIMENTATORE ELETTRONICO
DIMMERABILE STABILIZZATO 500mA
220-240V 50/60Hz
idoneo per il collegamento in serie
di max 2 Well o 4 Mini Well.

Max 10 alimentatori gestibili in PUSH con
uno o più pulsanti NA in parallelo
(non necessita di cavetti di sincronizzazione).

ELECTRONIC DIMMABLE
STABILIZED DRIVER 500mA
220-240V 50/60Hz
Suitable for the connection in series
of max 2 Well or 4 Mini Well.
Max 10 drivers manageable in PUSH
with one or more NO buttons in parallel
(no synchronization cables required).

CODE	POWER	A (mm)	D (mm)	H (mm)	L (mm)
101904.99	20W	52	58	26	156



KIT DI EMERGENZA
da installare sul controsoffitto
a lato del prodotto.

EMERGENCY KIT
to place on the false ceiling
next to the fixture.

CODE	TIME	A (mm)	D (mm)	H (mm)	L (mm)
18002.99	1h	46	59	23	138
18003.99	3h	80	92	45	212

Flusso in emergenza
Emergency flux

WELL 10W	67%
MINI WELL 5W	76%