



176

PONGO



LED

Proiettore LED orientabile, per installazione a binario elettrificato Eurostandard trifase Novatrack. Sorgenti LED warm white 3000K. Alta resa cromatica CRI >95. Disponibile con ottiche intercambiabili per emissione a 20° o 45°.

MATERIALI

Corpo cilindrico alettato in lega di alluminio pressofuso e vano accessori in estruso di alluminio, verniciati a polvere a finitura goffrata. Riflettori in alluminio con deposizione in alto vuoto di alluminio puro al 99,9%; adattatore plastico per binario trifase (incluso); vetro di protezione trasparente per IP40 (incluso).

CABLAGGIO

Alimentazione elettronica 220-240V 50/60 Hz integrata.

Adjustable LED projector for track mounting on electrified Eurostandard three-phase Novatrack. LED source warm white 3000K. High colour render index CRI >95. Available with interchangeable optics for 20° or 45° emission.

MATERIALS

Cylindrical finned body made of die-cast aluminium alloy and power supply box made of extruded aluminium, powder coated with embossed finish. Reflectors made of aluminium alloy with vacuum process deposition of pure 99,9% aluminium. Plastic adaptor for three-phase track (adaptor included). Transparent protection glass for IP40 included.

WIRING

Integrated electronic 220-240V 50/60Hz driver.

Pongo LED proiettore orientabile per installazione a binario elettrificato Novatrack
 alimentatore elettronico, adattatore per binario elettrificato Novatrack, riflettori 20° e 45°
 e vetro trasparente inclusi

Pongo LED adjustable spotlight for track mounting on electrified Novatrack
 electronic driver and adaptor for electrified Novatrack and interchangeable reflectors for 20° and 45°
 and transparent glass included

3000 K

Codice/Code	W led	fascio/beam	Flusso apparecchio (lm)/Fixture flux (lm)
100101. __	35	20°/45°	2618

LED

Riflettori intercambiabili 20°- 45° inclusi / Reflectors 20°-45° included



Vetro trasparente IP40 incluso / Transparent glass IP40 included



IP
40



- _01 - Bianco/White
- _02 - Nero/Black

