


SWI PLUS




Mini proiettore orientabile a LED IP67.
Disponibile con ottiche per emissione a fascio medio o largo.
Corpo in lega di alluminio anodizzata e verniciata a polvere;
staffa in acciaio inox AISI 316L; viteria in acciaio inox; schermo
piano in vetro temprato extrachiaro trasparente.
Lente in PMMA ottico.
Fornito di pressacavo in ottone nichelato e membrana
idrofobica in GORE-TEX e di cavo di alimentazione H05RN-F
2x1 mm² di L 500 mm; alimentazione separata, con
alimentatore elettronico stabilizzato 24Vdc 220-240V 50/60Hz.

LED IP67 adjustable compact projector.
Available with optics for medium or large beam emission.
Body made of anodized powder coated aluminium alloy;
bracket made of AISI 316L stainless steel; screws made of
stainless steel; flat screen made of transparent extra-clear
tempered glass.
Lens made of optical PMMA.
Complete with card grip made of nickel-plated brass and
hydrophobic membrane GORE-TEX and with H05RN-F 2x1
mm² L 500 mm
power supply cable separated, electronic stabilized driver
24Vdc 220-240V 50/60Hz.



BEAM	POWER	FLUX	3000K		FLUX	4000K	
20°	6W	527 lm	15901.03	.06	556 lm	15903.03	.06
60°	6W	514 lm	15902.03	.06	542 lm	15904.03	.06

ACCESSORI ACCESSORIES




PICCHETTO
per installazione in
terreno acciaio inox

STAKE for installation
in the ground stainless steel

CODE

A830K0001KK



ALIMENTATORE ELETTRONICO
stabilizzato 24Vdc
220-240V 50/60Hz

ELECTRONIC STABILIZED DRIVER
24Vdc 220-240V 50/60Hz

CODE

101301.99

101302.99

E182K0060KK

E182K0100KK

IP	POWER	A (mm)	D (mm)	H (mm)	L (mm)
20	45W	30	34	16	251
20	100W	30	35	18	320
67	60W	43	54	32	163
67	100W	52	64	37	190

