



THE PANEL IP65



LED

Apparecchio LED ultra-slim 600x600mm. Sorgenti LED warm white (3000K) e neutral white (4000K). Emissione diretta diffusa. Eccellente uniformità e confort visivo e alte performance con un risparmio energetico >50%. Grado di protezione IP65 totale. Installabile senza accessori ad incasso in appoggio in controsoffitti a pannelli 600x600mm con struttura a vista.

MATERIALI

Cornice in lega di alluminio verniciata a polvere di colore bianco; diffusore opale ad altissima trasmittanza, a luminanza uniforme.

CABLAGGIO

Alimentazione elettronica inclusa 220-240V 50/60Hz (alimentatore esterno al pannello LED da collegare ad esso tramite opportuni connettori rapidi).

LED ultra-slim fixture 600x600. LED sources warm white 3000K and neutral white 4000K.

Direct diffused global emission. Excellent uniformity and visual comfort and high performance with energy saving >50%. Global protection index IP65.

Recessable without accessories in panelled 600x600 visible-structure false ceilings.

MATERIALS

Frame made of aluminium alloy, white powder coated. Opal high-transmittance and uniform lighting diffuser

WIRING

electronic driver included 220-240V 50/60Hz (external driver, to be connected to the LED panel by rapid connectors).

The Panel IP65 600x600mm alimentatore elettronico incluso. Installabile esclusivamente ad incasso in appoggio in controsoffitti a pannelli 600x600mm con struttura a vista
The Panel IP65 600x600mm electronic driver included. Installed exclusively in recessed panelled 600x600 visible-structure false ceilings

3000 K

Codice/Code	W	Flusso apparecchio (lm)/Fixture flux (lm)
19301.01	38	2800

4000 K

Codice/Code	W	Flusso apparecchio (lm)/Fixture flux (lm)
19302.01	38	2900



_01 - Bianco/White

