

# THE PANEL IP65

ULTRA SLIM 38W - 2900 lm



COD. 19301.01 - 38W - 3000K - 2800lm

COD. 19302.01 - 38W - 4000K - 2900lm

\_.01 - Bianco/White



16

Apparecchio LED ultra-slim 600x600mm. Sorgenti LED warm white (3000K) e neutral white (4000K). Emissione diretta diffusa. Eccellente uniformità e confort visivo e alte performance con un risparmio energetico >50%. Grado di protezione IP65 totale. Installabile senza accessori ad incasso in appoggio in controsoffitti a pannelli 600x600mm con struttura a vista.

#### Materiali

Cornice in lega di alluminio verniciata a polvere di colore bianco; diffusore opale ad altissima trasmittanza, a luminanza uniforme.

#### Cablaggio

Alimentazione elettronica inclusa 220-240V 50/60Hz (alimentatore esterno al pannello LED da collegare ad esso tramite opportuni connettori rapidi).

LED ultra-slim fixture 600x600. LED sources warm white 3000K and neutral white 4000K. Direct diffused global emission. Excellent uniformity and visual comfort and high performance with energy saving >50%. Global protection index IP65. Recessable without accessories in panelled 600x600 visible structure false ceilings.

#### Materials

Frame made of aluminium alloy, white powder coated. Opal high-transmittance and uniform lighting diffuser

#### Wiring

Electronic driver included 220-240V 50/60Hz (external driver, to be connected to the LED panel by rapid connectors).

